









## Accessories DLS/FLS

Picture	Item No.	Description	Price / EUR
	500590	<b>Starter kit accessories DLS/FLS</b> Consisting of: - RS-232 cable (500200) - Power Supply → Not applicable for measuring devices with the heater! - Utility Software - Manual	100.00
	500001	<b>Calibration certificate</b> for new measuring devices DLS/FLS	90.00
	500002	<b>Recalibration with calibration certificate</b> for used measuring devices DLS/FLS	170.00
	500101	<b>View finder with support</b> for easy adjustment of the sensor, if aiming on targets far away applicable for DLS/FLS	194.00
	500113	<b>Reflective plate 210 x 297 mm (orange)</b> applicable distance range: ~ 25 to 150m	46.00
	500114	<b>Reflective foil 600 x 1200 mm (orange)</b> for self fitting, applicable distance range: ~ 25 to 150m	156.00
	500200	<b>RS-232 Configuration cable DLS/FLS</b> Length = 3m, with 15 pin connector IP65 and 9 pin connector	55.00
	500202	<b>AO/DO Connection cable DLS/FLS</b> Length = 3m, with 15 pin connector IP65	46.00
	500203	<b>RS-422 Connection cable DLS/FLS</b> length = 5m, with 15 pin connector IP65	61.00
	500203/xxx	<b>RS-422 Connection cable - special length</b> Length = XXX m, with 15 pin connector IP65 applicable for DLS/FLS	Price on request
	500210	<b>Converter RS-232 to RS-422</b> IP20 module, mountable on 35 mm DIN rail applicable for DLS/FLS	138.00
	500213	<b>Alignment jig</b> Adjusting angle +/-7° in two directions Material: stainless steel (V2A) Recommended for distances up to 50m Applicable for EDS/DLS/FLS	49.00



### Accessories DLS/FLS

Picture	Item No.	Description	Price / EUR
	500214	<b>DIM5 Profibus Interface external</b> Profibus/RS-422 converter, IP20 module, mountable on 35 mm DIN rail applicable for DLS/FLS	335.00
	500215	<b>Numeric digital display 6 digits</b> Char. height 14mm; LED red; RS-232/485; Reading distance: 1...5m applicable for DLS/FLS	272.00
	500251	<b>Cover IP65 for 15 pin D-Sub connector</b> applicable for DLS/FLS	49.00
	500253	<b>Connector 90° IP65 for 15 pin D-Sub connector</b> maximum cable diameter is 5 mm applicable for DLS/FLS	71.00
	500290	<b>Connector straight IP65 for 15 pin D-Sub</b> cable diameter range 6 to 10 mm applicable for DLS/FLS	19.00
	500291	<b>Ferrite for cable diameter 6.5mm</b>	7.00
	500292	<b>Ferrite for cable diameter 10mm</b>	9.00
	500293	<b>Ferrite for cable diameter 13mm</b>	11.00

4. March 2011 / Subject to change without notice

Price List 2011\_DLS-C\_FLS-C\_EUR\_EN\_V1.odt